SMOKE ALARM BATTERY POWERED RF







BATTERY POWERED SMOKE ALARM10YR RF MODEL

Emerald's Battery Powered RF Smoke Alarm is powered by a 10 year non-replaceable lithium battery.

The alarm is fitted with a test/hush/silence button to facilitate testing of the alarm. The silence function also allows the alarm and alarm system to be silenced in the case of a false alarm.

This alarm can be used as a stand-alone alarm or can be connected with up to 40 alarms. This allows all smoke alarms connected to activate simultaneously.

Compatible with Emerald's radio frequency (RF) enabled products.

FEATURES

- 10 year non-replaceable lithium battery
- RF interconnectable with up to 40 alarms on one wireless network
- Indicator lights for test and fault warnings
- Hush function
- Loud alarm 85dB(A) @ 3m
- 48 hour memory function
- Meets Australian Smoke Alarm Standards (AS3786:2014)
- 10 year warranty

SPECIFICATIONS

MODEL NUMBER	EP-RANG-RF-10
DIMENSIONS	120 x 36.6mm
WEIGHT	146.6g
WARRANTY	10 Years
WIRELESS DISTANCE	>20m (100m outside)

	,, (= - =, (= - =,
MOUNTING OPTIONS	Ceiling or wall mount
INTERCONNECT	Built-in wireless radio frequency (RF) technology Connects with up to 40 Emerald RF enabled alarms
SENSOR	Photoelectric optical chamber
SOUND PATTERN	ISO 8201
ALARM VOLUME	>85dB(A) @ 3m
NORMAL OPERATING & STORAGE TEMPERATURE	0°C to 40°C
NORMAL OPERATING & STORAGE HUMIDITY	≤93% relative humidity (non-condensing)
COMPATIBILITY	RF smoke alarm is compatible with - • Emerald's radio frequency (RF) enabled alarms

Emerald SafeLink Wi-Fi gatewaySmoke Alarm Controller

POWER - BATTERY 10 year non-replaceable 3V lithium battery (EVE CR17450)



